

Kitemark™ Certificate

This is to certify that:

Veka plc
Farrington Road
Rossendale Road Industrial Estate
Burnley
BB11 5DA
United Kingdom

Holds Certificate Number:

KM 33520

In respect of:

BS EN 12608 / PAS24
PVCU Profile - Enhanced Security Windows System Supplier

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI:


Chris Lewis - Certification Director, Product Certification

First Issued: 1995-03-17

Latest Issue: 2020-06-03

Effective Date: 2020-06-03

Expiry Date: 2023-06-02

Page: 1 of 33



...making excellence a habit.™

Kitemark™ Certificate

No. KM 33520

BS EN 12608:2016 / PAS 24:2016 - General and enhanced security performance requirements for window assemblies.

This Certificate covers the following window system design specification. The following materials are also certificated for use with windows and doors in conjunction with BS 7412 and PAS 24 when foiled in accordance with BS 7722:2010: Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

Halo 70mm Rustique PVC-U Window System

Fabrication and Installation:	Fabricated and installed in accordance with the latest issue(s) of the following Veka plc controlled manual(s): 70mm System 10 and Rustique System Technical Manual.	
System description:	The windows are double glazed, internally or externally beaded*, multipoint locking, with welded transoms/mullions, tee joints and either welded or mechanically jointed outer frames. Windows are classified W. (* dependant on Window Type)	
Ventilation:	None	
Window Types:	Casement windows (inc. Smart, Twin, Flush & *Storm 2 Sash)	Securistyle Defender, Yale Std, DGS Elite, Nico Atlas Heavy Duty, Cotswold EZ or Cotswold Sinidex Friction Stays, Halo Security Claw, Securistyle Vector Excluder ASD2, Nico Xtra Bolt, GT Stayguard Elite SG036, Window Ware Kore and Maco Hinge Protectors, Roto TSL, Yale Rapide, Yale Encloser#, Yale Defender+, Nico Multilock, Nico Mk 2 Shootbolt, Maco Rail, Maco MK I, Maco MK II, Maco MSPAG Telescopic or Maco MSPAG Croppable espagnolette locking
	Parallel windows	Cotswold Sinidex Parallel Stays, Siegenia Titan perimeter locking.
	Tilt/Turn windows (inc.Smart Sash)	Roto NT Face Fix, Roto NT Designo; Maco MULTI-MATIC Face Fixed Hinge Security, Siegenia FAVORIT Si-line Face Fixed Hinge Security, Siegenia FAVORIT axxent Concealed Hinge Security
	Glazing	GT Securi-Clips, GT Snap-Lok
	Fixed Windows	
	Multilight windows comprising opening light(s) and/or fixed light(s)	
	*Storm 2 Sash = Limited Availability	
	# Yale Encloser maximum sash size 1300mm	
	+ Yale Defender requires R10271 strap plates for sash sizes 1401-1550mm	

First Issued: 1995-03-17
Latest Issue: 2020-06-03

Effective Date: 2020-06-03
Expiry Date: 2023-06-02

Kitemark™ Certificate

No. KM 33520

Halo 70mm Rustique PVC-U Window System Size Limitations and Performance Characteristics

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Area(m ²) - Maximum	Friction Stays (up to and including)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1
Sash dimensions for windows with approved outer sash profiles:									
Internally Glazed									
Projecting top hungs Part reinforced*	1178	1178	-	24"	-	4	E1050	4	1600
Projecting top hungs Smart Sash	1246	1446	-	24"	-	4	E1050	E2400	2400
Projecting top hung Mechanically jointed Flush Sash	1380	1380		24"		3	7A	BE2400	2400
Projecting top hungs Reinforced*	1400	1400	-	24"	-	3	7A	A3	1200
Projecting side hungs Part reinforced*	628	1278	-	16"	-	3	7A	4	1600
Projecting side hungs Reinforced*	800	1550	-	16"-	-	4	8A	A4	1600
Projecting side hungs Smart Sash	846	1746	-	16"	-	4	E1050	E2400	2400
Projecting side hung Mechanically jointed Flush Sash	846	1746		16"		3	7A	BE2400	2400
Projecting side hungs Flush Sash	620	1270	-	16"	-	4	9A	4	1600
Externally Glazed									
Projecting top hungs Part reinforced	1178	1178	-	24"	-	2	E1050	4	1600
Projecting side hungs Part reinforced	628	1278	-	16"	-	3	E900	4	1600

First Issued: 1995-03-17

Latest Issue: 2020-06-03

Effective Date: 2020-06-03

Expiry Date: 2023-06-02

Page: 22 of 33

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Kitemark™ Certificate

No. KM 33520

Halo 70mm Rustique PVC-U Window System Size Limitations and Performance Characteristics

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Area(m ²) - Maximum	Friction Stays (up to and including)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1
Sash dimensions for windows with approved sash profiles:									
Tilt/Turns reinforced	1414	1414	-	-	-	4	E1050	A4	1600
Tilt/Turns Smart Sash	1414	1414	-	-	-	4	E1050	A4	1600
Parallel sashes	1400	1550				3	8A	A4	1600
Overall dimensions for windows with approved outerframe profiles:									
Fixed Part reinforced*	3000	3000	9	-	-	4	E750	4	1600
Twin Sash	1250	1250	1.56	-	-	4	9A	E2400	2400
Overall dimensions for windows with approved outerframe & transom/mullion profiles:									
Multilights Unreinforced	1800	1800	1.8	-	1000	3	E750	4	1600
Multilights, 713155/S00155 T/M reinforcement	1662	1602	2.66	-	1602	4	8A	A4	1600
Multilights 713158/S00158 T/M reinforcement	2000	2000	2.7	-	1350	4	7A	4	1600
Multilights 713174/S00174 T/M reinforcement	1719	1634	2.81	-	1634	4	9A	A5	2000

*Inc. Storm 2 Casement Range = Limited Availability

First Issued: 1995-03-17

Latest Issue: 2020-06-03

Effective Date: 2020-06-03

Expiry Date: 2023-06-02

Page: 23 of 33

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.